

Split hole punch TriCut+™ for sheet steel (S235) and stainless steel

- 1 With 3-fold split
- 2 With UNF fine thread
- 3 With 4 crosshair markings for simple, central alignment



EDELSTAHL
STAINLESS STEEL

"The max. material thickness for which a hole punch can be used always depends on the screw and draw bolts used."

Usable up to a material thickness of:

- 2.5 mm steel sheet with 3/4" (19.0 mm) screw or draw bolt
- 2.0 mm steel sheet with 7/16" (11.1 mm) screw or draw bolt

Split hole punch TriCut+™ - sets



All sets are supplied in heavy-duty practical plastic cases.

Ø mm	15.2	16.2	18.6	19.0	20.4	22.5	25.4	28.3	30.5	31.7	32.5	34.6	37.0	38.0	40.5	43.2	47.0	49.6	50.5	54.0	60.0	61.5	63.5
Ø metric	-	M 16	-	-	M 20	-	M 25	-	-	-	M 32	-	-	-	M 40	-	-	-	M 50	-	-	-	M 63
Ø PG	9	-	11	-	13	16	-	21	-	-	-	-	29	-	-	-	36	-	-	42	48	-	-
Ø Inch	-	-	-	3/4"	-	7/8"	1"	-	1-7/32"	1-1/4"	-	-	-	1-1/2"	-	1-11/16"	-	1-15/16"	-	2-1/8"	-	2-3/8"	2-1/2"
Ø Conduit	-	-	-	-	-	1/2"	-	3/4"	-	-	-	1"	-	-	-	1 1/4"	-	1 1/2"	-	-	-	2"	-
Prod.-No.																							
01652		•			•		•				•				•								
01653		•			•		•				•				•				•				•
01645						•		•				•				•		•				•	
01646				•			•			•				•					•				

Ø in mm	Max. Material thickness in mm (VA)	Size Metric	Size PG	Size Inch		Size Conduit & Pipe Size				
							Punches and dies, draw bolt with ball bearing	Punches and dies	matching draw bolt	matching draw bolt with ball bearing
Prod.-No.										
15.2	2.0	-	9	-	0,598	-	01465	01600	02007	01342
16.2	2.0	M 16	-	-	0,638	-	01466	01656		
18.6	2.0	-	11	-	0,732	-	01467	01603		
20.4	2.0	M 20	13	-	0,803	-	01468	01606		
22.5	2.0	-	16	7/8"	0,886	1/2"	01469	01609		
25.4	2.5	M 25	-	1"	1,000	-	01470	01659		
28.3	2.5	-	21	-	1,114	3/4"	01471	01612	02002	01340
30.5	2.5	-	-	1-7/32"	1,201	-	01472	01615		
32.5	2.5	M 32	-	-	1,280	-	01473	01662		
34.6	2.5	-	-	1-11/32"	1,362	1"	01474	01618		
37.0	2.5	-	29	-	1,457	-	01475	01621		
40.5	2.5	M 40	-	-	1,594	-	01476	01665		
43.2	2.5	-	-	1-11/16"	1,701	1 1/4"	01477	01624		
47.0	2.5	-	36	-	1,850	-	01478	01627		
49.6	2.5	-	-	1-15/16"	1,953	1 1/2"	01479	01630		
50.5	2.5	M 50	-	-	1,988	-	01480	01668		
54.0	2.5	-	42	2-1/8"	2,126	-	01481	01633	01341	
60.0	2.5	-	48	-	2,362	-	01482	01636		
61.5	2.5	-	-	2-3/8"	2,421	2"	01483	01640		
63.5	2.5	M 63	-	2-1/2"	2,500	-	01484	01671		